PO Job Risk Assessment

Name(s) of Risk Team Members: R. Gill, K. Kusche, S. Shapiro, F. Zhou	Point Value → Parameter ↓	1	2	3	4	5	
Job Number or Job Identifier: PO-JRA-025	Frequency (B)	<u><</u> once/year	<pre><once month<="" pre=""></once></pre>	<pre><pre><pre><pre><pre><pre></pre></pre></pre></pre></pre></pre>	<pre><once pre="" shift<=""></once></pre>	>once/shift	
Job Description: Routine startup of ATF at beginning of operating day.	Severity (C)	First Aid Only	Medical Treatment	Lost Time	Partial Disability	Death or Permanent Disability	
Training and Procedure List (Optional): Date: Rev. #: 0	Likelihood (D)	Extremely Unlikely	Unlikely	Possible	Probable	Multiple	
Stressors (if applicable, please list all):	Reason for Re						

				Before Additional Controls							After Additional Controls					
Job Step / Task	Hazard	Control(s)	Stressors Y/N	# of People A		Severity C	Likelihood D	Risk* AxBxCxD	Control(s) Added to Reduce Risk	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	% Risk Reduction
Power up control computers, login and release keys	None	Follow startup procedure	N	1	4	1	1	4								
Walk facility to verify shielding locks and non-occupancy	Trips, falls due to congested passageways	Maintain good housekeeping and clear walkways	N	1	4	1	1	4								

Rev. 0 10/29/2004

PO Job Risk Assessment

				Before Additional Controls							Α					
Job Step / Task	Hazard	Control(s)	Stressors Y/N	# of People A	Frequency B		Likelihood D	Risk* AxBxCxD	Control(s) Added to Reduce Risk	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	% Risk Reduction
Start water chiller (temporary step until leak repaired)	Falls to lower level, electrical shock	Use non-skid step stool, or insulated pusher	N	1	4	1	1	4								
Switch 220 VAC breakers	Electrical shock, arc flash	Operator wears natural fiber jacket and safety glasses	N	1	4	2	1	8								
Further Description *Risk:	on of Controls Added to		41	to	60				61 to 80		81	or	area	ater		
MON.	Negligible	Acceptable		loderate			Substantial			81 or greater Intolerable						